Flexi Ridge

Hard-wearing ribbed matting ideal for standing work areas, production lines and packing stations.





Flexi Ridge's ribbed surface withstands light spills, protects delicate items and provides cushioning underfoot, making it ideal for workplaces where employees are on their feet and tools are in frequent use.

This excellent multi-purpose product provides good slip resistance, reduces the impact of noise and protects delicate items and tools from damage if dropped. Thanks to the mat's ribbed surface, It's also easy to maintain – the integral ridges means any liquid is easily dispersed, and the smooth surface can be wiped down.







Standard sizes:

Product	Flexi Ridge
Height	2.8mm (7/16'')
Standard roll options	2 x lm (65'7'' x 3'3'')
Weight	2.45 kg/m2 (0.50 lbs/sq.ft)

Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (+/- 1cm)
Flexi Ridge	2.8 mm	20 m	100 cm
			'

All dimensions are nominal

Technical information:

Chemical	Resistant to most acids, alkalines and oils.	
Composition	Flexible Polyvinyl Chloride (PVC)	
Environment	Flexi Ridge is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.	
Fire	EN 13501-1:2007-Bfl-S1	
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.	
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.	
UV light	Resistant to PVC degradation.	
Warranty	One year.	

Installation:

Flexi Ridge's one-piece construction means installation is simple:

- Supplied in convenient roll format
- Easy to cut to size and shape
- Contours to uneven surfaces

Cleaning:

Keeping Flexi Ridge looking good is easy:

- Light to handle
- Simply lift or roll to clean
- Easy to wipe clean

