



Heavy-duty matting with an aggressive surface designed for industrial workplaces.



Extra-aggressive matting capable of withstanding even the toughest industrial environments, Flexigrid is ideal for workplaces where spillages, debris and metal shards are an issue.

The mat's diamond-tread surface provides the highest slip resistance, while the elevated height means any hazardous matter is quickly dispersed and drained. It's also perfect for workplaces with standing employees: the two-layer construction provides comfortable cushioning to help reduce fatigue in industrial environments.



Features:

				
Diamond-tread surface	Two-layer construction	Proven anti-fatigue properties	Made from flexible PVC	Comes in 5m and 10m rolls or ramped modules



Benefits:

				
Certified slip resistant (DIN 51130:R11, ASTM 1677:0.6/0.5)	Excellent drainage (DIN 51130:V10)	Boosts productivity	Cut to fit on site, contours to uneven surfaces	Quick to install, easy to clean



Standard sizes:

Product	Flexigrid
Height	20mm (3/4")
Standard roll options	5 x 0.6m (16'6" x 2')
	5 x 0.91m (16'6" x 2')
	10 x 0.6m (33' x 2')
	10 x 0.91m (33' x 3')
Standard module options	1.8 x 0.6m (6' x 2')
	1.8 x 0.91m (6' x 3')
Weight	9.8kg/m ² (2 lbs/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (+/- 1cm)
Flexigrid	20mm	1.8m 5m 10m	60cm 91cm

All dimensions are nominal

Technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils.
Composition	Made from flexible Polyvinyl Chloride (PVC).
Environment	Flexigrid is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products..
Fire	DIN 4102 Part 1- Classification B2
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.
Slip resistance	ASTM F 1677- Dry/Wet: 0.6/0.6 DIN 51130: R11, V10
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Four years.

Installation:

Flexigrid's one-piece construction means installation is simple:

- Comes in 5m and 10m rolls, or choose ramped modules
- Easy to cut to fit on site
- Contours to uneven surfaces

Cleaning:

Keeping Flexigrid looking good is easy:

- Light to handle
- Roll or lift to clean
- Easy to clean with a high pressure hose

Colours:



Black

More colours
available
upon request

Ancillaries:

> **Flexigrid**

Aluminium edging (H: 20mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodised aluminium. Size: 20mm x 50mm x 2m (7/8" x 2 3/16" x 6'6")

Connector clips: dual purpose (H: 25mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10