

# Frontrunner SB+



Solid-backed entrance matting with carpet inserts for maximum moisture removal in internal areas.



The superhero of the entrance matting world, Frontrunner SB+ is a low-profile, solid-backed mat that requires no recessed mat well.

Simply roll out, cut to fit and lay within your existing carpet tiles or luxury vinyl tiles – no mat well needed. You can also place directly on your current floor with ramped PVC edges to create a slip-resistant walkway. The mat's etched pattern removes debris and the heavy-duty absorbent inserts dries any moisture, helping to reduce the amount of dirt walked into the building. Wheel-and-heel proof with excellent rolling resistance, it's perfect for commercial buildings and shopping centers with high traffic.



### Features:



Etched pattern



One layer hollow construction



Ribbed vinyl pattern with solid backing




6.5mm grid height




Close mesh grid




### Benefits:




Certified slip resistant (DIN 51130: R11, ASTM C1028: 0.6/0.6)




Light to handle



Easy to install, no need for recessed mat well



Loose lay or adhere to subfloor



Wheel-and-heel proof



# Frontrunner SB+

## Data sheet



### Standard sizes:

<b>Product</b>	<b>Frontrunner SB+</b>
<b>Height</b>	6.5/8mm (1/4"-5/16")
<b>Standard roll options</b>	10 x 1m (33' x 3'3")
<b>Standard module option</b>	1 x 1.5m (3'3" x 4'11")
<b>Weight</b>	6.3 kg/m2 (1.3lb/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

### Tolerances:

	<b>Height (+/- 0.5mm)</b>	<b>Length (0+0.3m)</b>	<b>Width (0+2cm)</b>
<b>Frontrunner SB+</b>	6.5/8 mm	10 m	100 cm

All dimensions are nominal

### Technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Chemical</b>	Resistant to most acids, alkalines and oils.
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Environment</b>	We don't use any substances included in the SVHC list under REACH in any of our matting products.
<b>Fire</b>	EN ISO 13501-1:2007-Cfl-S1, ASTM E648 – Class 2
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.
<b>Rolling resistance</b>	ASTM F 2753: 0.080in loss of thickness after 1,000 cycles at 500lb
<b>Slip resistance</b>	DIN 51130: R11, V10
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>UV light</b>	Resistant to PVC degradation
<b>Warranty</b>	Three years.

### Installation:

Frontrunner SB+'s one-piece construction means installation is simple.

There are two ways to install SB+: adhere or loose lay. For large installations with medium to high traffic, we recommend adhering your mat.

### Cleaning:

Keeping Frontrunner SB+ looking good is easy:

- Lightweight
- Simply roll or lift to clean
- No special tools needed
- Quick and easy to vacuum

# Frontrunner SB+


## Product data sheet



### Colours:



Black



Grey

More colours  
available  
upon request


### Carpets:



Black 608



Dark grey 607



Grey 606

### Ancillaries:

#### PVC edging (SB / SB+)



Supplied in rolls of 60m (197") length with cold welding paste. Comes in black and dark grey. Size: 6.5mm x 30mm x 60m (1/4" x 1" x 197")

#### PVC joining strip (SB / SB+)



Can be welded to join rolls end-to-end or side-to-side when doing large installations. Comes in black. Size: 3.5mm x 3.6m (1/8" x 11'9")