

Frontrunner SB

Solid-backed entrance matting designed for internal and external areas with no mat well.



Frontrunner SB is a low-profile, solid-backed mat that can be loose laid to integrate easily with your existing floor coverings.

Simply roll out, cut to fit and lay within your existing carpet tiles or luxury vinyl tiles – no mat well needed. You can also place directly on your current floor with ramped PVC edges to create a slip-resistant walkway. The mat's ribbed pattern scrapes shoes and wheels clean, while the grid traps and collects any debris, helping to reduce the amount of dirt walked into the building. Wheel-and-heel proof with excellent rolling resistance, it's perfect for commercial buildings and shopping centres with high traffic.



Features:

Etched pattern

One layer hollow construction

Ribbed vinyl pattern with solid backing

6.5mm grid height

Close mesh grid



Benefits:

Certified slip resistant
(DIN 51130: R11, ASTM C1028: 0.6/0.6)

Light to handle

Easy to install, no need for recessed mat well

Loose lay or adhere to subfloor

Wheel-and-heel proof



Frontrunner SB

Data sheet



Standard sizes:

Product	Frontrunner SB
Height	6.5mm (1/4")
Standard roll options	10 x 1m (33' x 3'3")
Weight	6.3 kg/m ² (1.3lb/sq.ft)

Tolerances:

	Height (+/- 0.5mm)	Length (0+0.3m)	Width (0+2cm)
Frontrunner SB	6.5mm	10m	100cm

All dimensions are nominal

Technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils.
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	Frontrunner SB is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products.
Fire	EN ISO 13501-1:2007-Cfl-S1, ASTM E648 – Class 2
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.
Rolling resistance	ASTM F 2753: No apparent damage to the vinyl portion of the system after 1,000 cycles at 500lbs
Slip resistance	DIN 51130:RI I, VI0 ASTM F C1028 - Dry/Wet: 0.6/0.6
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Three years.

Installation:

Frontrunner SB's one-piece construction means installation is simple.

There are two ways to install SB: adhere or, for modules, loose lay. For large installations with medium to high traffic, we recommend adhering your mat.

Cleaning:

Keeping Frontrunner SB looking good is easy:

- Light to handle
- Simply roll or lift to clean
- No special tools needed
- Quick and easy to clean because of the solid backing

Frontrunner SB


Data sheet



Colours:



Black



Grey

More colours
available
upon request

Ancillaries:

PVC edging (SB / SB+)



Supplied in rolls of 60m (197") length with cold welding paste. Comes in black and dark grey. Size: 6.5mm x 30mm x 60m (1/4" x 1" x 197')

PVC joining strip (SB / SB+)



Can be welded to join rolls end-to-end or side-to-side when doing large installations. Comes in black. Size: 3.5mm x 3.6m (1/8" x 11'9")